

PRESVAC

POWER VAC

PD Blower Wet / Dry Vacuum Loader

Full Vacuum (28HG) , 3500 — 6600 CFM
Code Waste (Debris) Tank: ASME, DOT 407/412, TC 407/412, Dual DOT/TC, 35 PSI Max
Non-Code Waste (Debris) Tank: Heavy Duty Construction, Relief @14.5 PSI
Material: Carbon Steel, SS 304, SS 316, SS 316 High Polish
Modular Filtration Optimized To Blower & Application
Popular Options: Boom, Pressure Off-Load, Water Pump, Sound Proofing, Heated Valves



The Presvac Powervac is the ultimate PD Blower Wet / Dry Vacuum Loader. Operate as an air mover for dry applications or use full vacuum and extreme recovery rates for the toughest liquid, sludge and slurry jobs. The material knock out features in the Powervac debris tank minimize carry over. Heavy duty modular filtration configured to blower size and application provides superior blower protection and minimal maintenance.

PRESVAC

*THE GLOBAL LEADER IN MOBILE
VACUUM SYSTEMS*

*PRESVAC SYSTEMS BURLINGTON LTD.
4131 MORRIS DRIVE
BURLINGTON, ON, CANADA L7L 5L5
TOLL FREE: 1-800-387-7763
LOCAL: 1-905-637-2353
FAX: 1-905-681-0411*

WEB: WWW.PRESVAC.COM

EMAIL: SALES@PRESVAC.COM

POWERVAC 3800

Blower: Hibon SIAV 840*
Free Air: 3800 CFM, 3300 @ 18" HG, 1600 @ 27" HG
Driven Via: OMSI Heavy Duty Transfer Case
Code: DOT 407/412 (Hazardous Waste)
Tank Size: 16 Cubic YDS, 3250 USG, 2700 IMP
Tank Material: Carbon Steel SA36
Options: Acoustic Enclosure, With Insulated Storage
PV750 Pressure Off-Load, 35 PSI

*Roots DVJ 721 and Robuschi RBDV 125 are comparable blowers.



POWERVAC 5300

Blower: Hibon SIAV 8702*
Free Air: 5300 CFM, 4600 @ 18" HG, 2950 @ 27" HG
Driven Via: OMSI Heavy Duty Transfer Case
Code: DOT 407/412 (Hazardous Waste)
Tank Size: 16 Cubic YDS, 3250 USG, 2700 IMP
Tank Material: Stainless Steel 316 With High Polish
Options: Acoustic Enclosure, With Insulated Storage
PV750 Pressure Off-Load, 35 PSI
8" Power Rotation Loading Boom (DOT/TC)

*Roots DVJ 1021 and Roots Trinidad 1125T are comparable blowers.



POWERVAC 6400

Blower: Robuschi RBDV 145*
Free Air: 6200 CFM, 5100 @ 18" HG, 2900 @ 27" HG
Driven Via: OMSI Heavy Duty Transfer Case
Code: Dual TC/DOT 407/412 (Hazardous Waste)
Tank Size: 16 Cubic YDS, 3250 USG, 2700 IMP
Tank Material: Stainless Steel 316 With High Polish
Options: Acoustic Enclosure, With Insulated Storage
8" Power Rotation Loading Boom (DOT/TC)
Heated Valves
Custom Hometrays, Skirting & Tool Boxes

*Hibon 8902 is a comparable blower.

Options:

20" Top Manway - Rear Loading Port - Tank Anti-Surge Baffle - 8" Power Rotation Loading Boom
Pressure Unloading System - Pneumatic Unloading System - High Pressure Water Pump - High Rail
Acoustic Enclosure - Heated Valves - HEPA Filter Hook Up Ports - Transfer Pump - Walk Way Railing (42")
Custom Hose Trays And Tool Boxes - Two Tone Paint - Tank Striping - Many Other Options Available



THE GLOBAL LEADER IN MOBILE
VACUUM SYSTEMS

PRESVAC SYSTEMS BURLINGTON LTD.
4131 MORRIS DRIVE
BURLINGTON, ON, CANADA L7L 5L5
TOLL FREE: 1-800-387-7763
LOCAL: 1-905-637-2353
FAX: 1-905-681-0411

WEB: WWW.PRESVAC.COM

EMAIL: SALES@PRESVAC.COM