



PD Blower Wet / Dry Vacuum Loader

Air Flow: 3800, 5300 or 6400 CFM Full Vacuum (28HG) **Modular Filtration Optimized To Blower & Application** Blower Drive: OMSI Heavy Duty Transfer Case Code Tank Options : ASME, DOT 407/412, TC 407/412, Dual DOT/TC, 35 PSI Max Non-Code Tank Options: Heavy Duty Construction, Relief @14.5 PSI Tank Material Options: Carbon Steel, SS 304, SS 316, SS 316 High Polish



The Presvac Powervac is the ultimate PD Blower Wet / Dry Vacuum Loader. Operate as an air mover for dry applications or use full vacuum and extreme recovery rates for the toughest liquid, sludge and slurry jobs. The material knock out features in the Powervac debris tank minimize carry over. Heavy duty modular filtration configured to blower size and application provides superior blower protection and minimal maintenance.



THE GLOBAL LEADER IN MOBILE VACUUM SYSTEMS, SINCE 1972 PRESVAC SYSTEMS BURLINGTON LTD. 4131 MORRIS DRIVE BURLINGTON, ON, CANADA L7L 5L5 TOLL FREE: 1-800-387-7763 LOCAL: 1-905-637-2353 FAX: 1-905-681-0411

WEB: WWW.PRESVAC.COM

FMAIL: SALES@PRESVAC.COM

POWERVAC 4000

Blower: Hibon SIAV 840XL* Free Air: 4000 CFM, 3300 @ 18" HG, 1600 @ 27" HG Code: DOT 407/412 (Hazardous Waste) Tank Size: 16 Cubic YDS, 3250 USG, 2700 IMP Tank Material: Stainless Steel 316 High Polish

Options: PV750 Pressure Off-Load, 35 PSI Wash Down Pump: 5 GPM @ 2000 PSI 100 USG Gallon Water Tank

* Robuschi RBDV 125 is a comparable blower.



POWERVAC 5300

Blower: Hibon SIAV 8702 Free Air: 5300 CFM, 4600 @ 18" HG, 2950 @ 27" HG Code: DOT 407/412 (Hazardous Waste) Tank Size: 16 Cubic YDS, 3250 USG, 2700 IMP Tank Material: Carbon Steel SA36

Options: Acoustic Enclosure, With Insulated Storage PV750 Pressure Off-Load, 35 PSI 8" Power Rotation Loading Boom (DOT/TC)



POWERVAC 6400

Blower: Robuschi RBDV 145* Free Air: 6200 CFM, 5100 @ 18" HG, 2900 @ 27" HG Code: Dual TC/DOT 407/412 (Hazardous Waste) Tank Size: 16 Cubic YDS, 3250 USG, 2700 IMP Tank Material: Carbon Steel SA36

Options: Jurop PNR102 Pressure Off-Load 8" Power Rotation Loading Boom (DOT/TC) Heated Valves



*Hibon 8902 is a comparable blower.

Options:

20" Top Manway - Rear Loading Port - Tank Anti-Surge Baffle - 8" Power Rotation Loading Boom Pressure Unloading System - Pneumatic Unloading System - High Pressure Water Pump - High Rail Acoustic Enclosure - Heated Valves - HEPA Filter Hook Up Ports - Transfer Pump - Walk Way Railing (42") Custom Hose Trays And Tool Boxes - Two Tone Paint - Tank Striping - Many Other Options Available



THE GLOBAL LEADER IN MOBILE VACUUM SYSTEMS, SINCE 1972
 PRESVAC SYSTEMS BURLINGTON LTD.

 4131 MORRIS DRIVE

 BURLINGTON, ON, CANADA L7L 5L5

 TOLL FREE: 1-800-387-7763

 LOCAL:
 1-905-637-2353

 FAX:
 1-905-681-0411

WEB: WWW.PRESVAC.COM

EMAIL: SALES@PRESVAC.COM