

POWERVACWith Dump Chutes

PD Blower Wet / Dry Vacuum Loader

WEB: WWW.PRESVAC.COM

FMAIL: SALES@PRESVAC.COM

Air Flow: 3800, 5400 or 6400 CFM Full Vacuum (28HG)

Modular Filtration Optimized To Blower & Application Blower Drive: OMSI Heavy Duty Transfer Case

Code Waste (Debris) Tank: ASME, DOT 412, TC 412, Dual DOT/TC, 35 PSI Max Non-Code Waste (Debris) Tank: Heavy Duty Construction, Relief @15 PSI Material: Carbon Steel, SS 304, SS 316, SS 316 High Polish



The Presvac Powervac is the ultimate PD Blower Wet / Dry Vacuum Loader. Operate as an air mover for dry applications or use full vacuum and extreme recovery rates for the toughest liquid, sludge and slurry jobs. The material knock out features in the Powervac debris tank minimize carry over. Heavy duty modular filtration configured to blower size and application provides superior blower protection and minimal maintenance.





PD Blower: Hibon VTB840XL, Max. Vacuum: 28" HG, Free Air: 4000 CFM, 15"HG: 3400 CFM, 27" HG: 1600 CFM. Single Baghouse With 29 Bags, Single Cyclone, 12" Dump Chutes SS 304, Heavy Duty Spring Tensioned Bolts Allow For Adjustment To Maintain Leak Proof Sealing. Dump Chute Doors Open With Debris Tank Door.



PD Blower: Hibon SIAV8702, Max. Vacuum: 28" HG, Free Air: 5300 CFM, 15"HG: 4700 CFM, 27" HG: 3000 CFM. Single Baghouse With 53 Bags, Two Cyclones, 12" Dump Chutes SS 304, Heavy Duty Spring Tensioned Bolts Allow For Adjustment To Maintain Leak Proof Sealing. Dump Chute Doors Open With Debris Tank Door.



BURLINGTON, ON, CANADA L7L 5L5 TOLL FREE: 1-800 -387-7763

LOCAL: 1-905-637-2353